



T-stuk dubbel stromend DIN 11852

DN	Inch	A	B	C	D	kg
	1"	26.50	22.90	25.40	53.00	0.10
	1 1/2"	45.00	35.10	38.10	90.00	0.21
DN 25		50.00	25.00	28.00	100.00	0.10
DN 25		50.00	26.00	29.00	100.00	0.10
DN 32		55.00	31.00	34.00	110.00	0.13
DN 32		55.00	32.00	35.00	110.00	0.13
DN 40		60.00	37.00	40.00	120.00	0.21
DN 40		60.00	38.00	41.00	120.00	0.21
	2"	67.50	47.80	50.80	135.00	0.29
DN 50		70.00	49.00	52.00	140.00	0.29
DN 50		70.00	50.00	53.00	140.00	0.29
DN 65		80.00	66.00	70.00	160.00	0.62
	2 1/2"	82.50	60.20	63.50	165.00	0.62
DN 80		90.00	81.00	85.00	180.00	0.85
	3"	95.00	72.80	76.10	190.00	0.85
DN 100		100.00	100.00	104.00	200.00	1.62
	4"	133.50	97.40	101.60	267.00	1.59
DN 125		187.00	125.00	129.00	374.00	2.71
DN 150		225.00	150.00	154.00	550.00	3.88