




**mulder**  
RVS PRODUCTS



Walsbocht 90° BL DIN 11852 304(L) / 316(L)

| D<br>mm | S<br>mm |        |          | R<br>mm     | kg   |
|---------|---------|--------|----------|-------------|------|
| 12.00   | 1.50    | DN 10  | DIN      | 26.00       | 0.02 |
| 13.00   | 1.50    | DN 10  | DIN R2   | 26.00       | 0.02 |
| 18.00   | 1.50    | DN 15  | DIN      | 35.00       | 0.04 |
| 19.00   | 1.50    | DN 15  | DIN R2   | 35.00       | 0.04 |
| 22.00   | 1.50    | DN 20  | DIN      | 40.00       | 0.06 |
| 23.00   | 1.50    | DN 20  | DIN R2   | 40.00       | 0.06 |
| 25.00   | 1.20    | 1.0"   | SMS 3008 | 32.00       | 0.03 |
| 25.40   | 1.25    | 1.0"   | INCH     | 27.50/37.00 | 0.03 |
| 25.40   | 1.60    | 1.0"   | BS 4825  | 38.00       | 0.06 |
| 28.00   | 1.50    | DN 25  | DIN      | 50.00       | 0.09 |
| 29.00   | 1.50    | DN 25  | DIN R2   | 50.00       | 0.09 |
| 31.80   | 1.25    | 1 1/4" | INCH     | 35.00/48.00 | 0.06 |
| 34.00   | 1.50    | DN 32  | DIN      | 55.00       | 0.11 |
| 35.00   | 1.50    | DN 32  | DIN R2   | 55.00       | 0.11 |
| 38.00   | 1.20    | 1 1/2" | SMS 3008 | 45.00       | 0.11 |
| 38.10   | 1.50    | 1 1/2" | INCH     | 45.00/52.00 | 0.11 |
| 38.10   | 1.60    | 1 1/2" | BS 4825  | 57.00       | 0.14 |
| 40.00   | 1.50    | DN 40  | DIN      | 60.00       | 0.14 |
| 41.00   | 1.50    | DN 40  | DIN R2   | 60.00       | 0.14 |
| 51.00   | 1.25    | 2.0"   | SMS 3008 | 72.00       | 0.20 |
| 50.80   | 1.50    | 2.0"   | INCH     | 67.50/75.00 | 0.22 |
| 50.80   | 1.60    | 2.0"   | BS 4825  | 75.00       | 0.22 |
| 52.00   | 1.50    | DN 50  | DIN      | 70.00       | 0.22 |
| 53.00   | 1.50    | DN 50  | DIN R2   | 70.00       | 0.22 |
| 63.50   | 1.50    | 2 1/2" | INCH     | 82.50       | 0.29 |
| 63.50   | 1.60    | 2 1/2" | SMS 3008 | 82.50       | 0.29 |
| 70.00   | 2.00    | DN 65  | DIN      | 80.00       | 0.40 |
| 76.10   | 1.60    | 3.0"   | INCH     | 96.00       | 0.50 |
| 76.10   | 2.00    | 3.0"   | SMS 3008 | 85.00       | 0.50 |
| 85.00   | 2.00    | DN 80  | DIN      | 90.00       | 0.57 |
| 101.60  | 2.00    | 4.0"   | INCH     | 133.00      | 1.10 |
| 101.60  | 2.00    | 4.0"   | INCH     | 152.00      | 1.10 |
| 104.00  | 2.00    | DN 100 | DIN      | 100.00      | 1.10 |

Zowel in matte uitvoering als in geslepen uitvoering leverbaar.